



Software Defined Radio for Highly Integrated System Architecture

CRIAQ Project AVIO-505

Abstract

- ◆ Integration of navigation, communication and surveillance systems under a single universal reconfigurable platform
- ◆ Establishment of an optimized integrated system to eliminate redundant hardware, generating substantial weight reduction and significant power consumption diminution
- ◆ Development of a software radio platform for multipurpose aeronautics and aerospace applications
- ◆ Demonstrate the benefits of ICT in efforts to reduce GHG
- ◆ Demonstrate the multiples advantages of integrating current and future applications such as DME, Transponder Mode S, Wide Band Radio and ADS-B within a single box
- ◆ Generic multi-system redundancy built into the antenna



Objectives

- ◆ Demonstrate the capabilities and performance of software defined radios (SDR) in aerospace
- ◆ Reduce the weight and use of equipment
- ◆ Reducing the number of radios, Coax cables and antennas by rethinking costly redundancies
- ◆ Reduction of overall wiring required for navigation, communication and surveillance systems interconnections, and number of distinct systems units
- ◆ Reduce the number of parts increasing reliability and safety at the system level
- ◆ Reduce GHG emissions by reducing the systems power consumption, and onboard systems weights
- ◆ Optimize and reduce the development and integration time of new system using a common platform
- ◆ Reduction of onboard electromagnetic fields (or HIRF) generated by multiple high power consumption systems

Technological benefits



Environmental

- ◆ The first project based on the needs of industry, then by the Greening ICT by reducing the weight of the aircraft, it reduces their need for fuel which contributes to a significant reduction of GHG emissions
- ◆ Minimum hardware replacement and recycling via software applications upgrades for improved or new functionalities

Original Equipment Manufacturer

- ◆ Reducing costs and development time of new equipment via a single platform, innovative and reconfigurable
- ◆ Reduction of certification and integration efforts for new applications
- ◆ Simplified repair and maintenance

Retrofit Applications

- ◆ Replace the expensive legacy avionics with additional applications
- ◆ Provide a low-cost growth path for future upgrades

Regulatory Evolution

- ◆ Addresses new operational standards such as NextGen
- ◆ Supporting automated airspace concept based on Automated Airspace Computer System (AACS)



Demonstrated Avionic Technologies

◆ DME



The Distance Measuring Equipment (DME) provides information on the line-of-sight distance from the aircraft to the ground station. The airborne DME equipment operates at 1025MHz to 1150MHz with a bandwidth of 126MHz, which is further divided into 126 channels with a bandwidth of 1MHz. Using different transmission scheme called mode X and mode Y doubles the number of channels.



◆ Mode S Transponder

The Mode S (S for Select) Transponder has been designed as an evolutionary addition to the Air Traffic Control Radar Beacon System (ATCRBS) to provide the enhanced surveillance and communication capability required for Air Traffic Control (ATC) automation. Mode S performs all the functions of Mode A and C transponders, and has data link capability. Mode S Transponder specific advantages:

- ◆ Surveillance of a large number of aircraft with better accuracy and increased surveillance reliability
- ◆ High degree of data integrity in ground-to-air, air-to-ground and air-to-air data link
- ◆ In TCAS equipped aircraft, the TCAS transmits coordination/interrogations to the other aircraft via the Mode S link in order to ensure the selection of complementary Resolution Advisories

◆ Wide Band Radio (WBR)

Another target of the AVIO-505 project is a SDR based air-to-satellite, air-to-air and air-to-ground (A/G) wide-band communication link whose specifications are still up to define. Basically there are two questions need to be answered before creating the design requirements. The first thing is what kind of satellite will it talk to and the second question is what data rate is regarded as wide-band.

◆ ADS-B



The Automatic Dependent Surveillance – Broadcast (ADS-B) is an Air Traffic Management (ATM) Surveillance system that replaces traditional radar based systems. ADS-B is like a large wireless network where the ground stations are Wireless Access Points and the aircraft are Clients. Aircraft report their own position via the network and receive back, from the ground system, traffic and other information. Computers on the ground integrate all the information and provide controllers with timely warnings of problems.

Institutional partners



Industrial partners



Contact

René Jr. Landry
ETS, 1100 Notre-Dame Street West
Montreal, Quebec, Canada, H3C 1K3
+1 (514) 396-8506
ReneJr.Landry@etsmtl.ca

